

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
 Issue date: 3/26/2020 Revision date: 3/11/2024 Supersedes: 3/29/2023 Version: 1.3
 SDS No: 12236-0035

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Rubisol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Cleaner

1.2.2. Uses advised against

Restrictions on use : For professional users only

1.3. Details of the supplier of the safety data sheet

Rey Chemie AG
 Pilatusstrasse 31
 5630 Muri
 Switzerland
 T +41 56 664 11 28
info@reychemie.ch

1.4. Emergency telephone number

Emergency number : NATIONAL: Tox Info Suisse: Tel. 145 (24 h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) : 

Signal word (CLP) : Danger

Contains : Naphtha (petroleum), hydrodesulfurized heavy; Solvent naphtha (petroleum), light arom.; 1-methoxy-2-propanol; monopropylene glycol methyl ether

Hazard statements (CLP) : H226 - Flammable liquid and vapour.
 H304 - May be fatal if swallowed and enters airways.
 H315 - Causes skin irritation.

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

Precautionary statements (CLP)	H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects. : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. P332+P313 - If skin irritation occurs: Get medical advice/attention. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Extra phrases	: Restricted to professional users. Restricted to professional users.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha (petroleum), hydrodesulfurized heavy Substance with a Community workplace exposure limit	CAS-No.: 64742-82-1 EC-No.: 265-185-4 EC Index-No.: 649-330-00-2	75 - 100	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
Solvent naphtha (petroleum), light arom.	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	2,5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
1-methoxy-2-propanol; monopropylene glycol methyl ether Substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	2,5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
ammonium hydroxide	CAS-No.: 1336-21-6 EC-No.: 215-647-6 EC Index-No.: 007-001-01-2	1 - 2,5	Skin Corr. 1B, H314 STOT SE 3, H335 Aquatic Acute 1, H400

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
ammonium hydroxide	CAS-No.: 1336-21-6 EC-No.: 215-647-6 EC Index-No.: 007-001-01-2	(5 \leq C < 100) STOT SE 3, H335

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment. Take affected person away from danger area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If symptoms persist, call a physician. In case of loss of consciousness, place the victim in the recovery position.
First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. Treat subsequently with skin cream. Get medical advice if skin irritation persists.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Attention. Beware, danger of aspiration. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.
Symptoms/effects after skin contact	: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: Product is not explosive.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Hydrogen chloride. Carbon oxides (CO, CO ₂). Phosgene.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
Other information	: Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No flames, no sparks. Eliminate all sources of ignition. Avoid contact with eyes, skin or mucous membrane. Evacuate the danger area.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No flames, no sparks. Eliminate all sources of ignition. Evacuate unnecessary personnel. Wear personal protective equipment.
----------------------	---

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Avoid contact with eyes, skin or mucous membrane. Do not breathe vapour/aerosol.
Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Explosion free apparatus have to be used. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Vapours are heavier than air and may spread along floors. Avoid formation of aerosols.
Hygiene measures : Do not inhale vapour. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Treat subsequently with skin cream. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed in a dry, cool and well-ventilated place. Pay attention to explosion protection guidelines.
Incompatible products : Oxidizing agent.
Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.
Storage area : Keep out of frost.

Switzerland

Storage class (LK) : LK 3 - Flammable liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

Switzerland - Occupational Exposure Limits

Local name	1-Méthoxypropan-2-ol [1-Méthoxy-2-propanol, Méthoxy-1-propanol-2] / 1-Methoxypropan-2-ol [Propylenglykol-1-methylether, 2PG1ME, 1-Methoxy-2-propanol]
------------	---

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
MAK (OEL TWA)	360 mg/m ³
	100 ppm
KZGW (OEL STEL)	720 mg/m ³
	200 ppm
Notation	SS _C , B / SS _C , B
Remark	B SS _C - ZNS, Auge ^{KT HU}
Regulatory reference	www.suva.ch, 01.01.2024
Switzerland - BAT	
Local name	1-Méthoxypropan-2-ol / 1-Methoxypropan-2-ol
BAT	20 mg/l (221.9 µmol/l; Paramètre biologique: 1-Méthoxypropanol-2; Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail.) / (221.9 µmol/l; Biologischer Parameter: 1-Methoxypropanol-2; Untersuchungsmaterial: Urin; Probenahmezeitpunkt: Expositionsende, bzw. Schichtende.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte
ammonium hydroxide (1336-21-6)	
Switzerland - Occupational Exposure Limits	
Local name	Ammoniac / Ammoniak
MAK (OEL TWA)	14 mg/m ³
	20 ppm
KZGW (OEL STEL)	28 mg/m ³
	40 ppm
Notation	SS _C / SS _C
Remark	NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2024

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Pay attention to explosion protection guidelines.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Protective goggles (EN 166)

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

8.2.2.2. Skin protection

Skin and body protection:

Solvent-resistant protective clothing

Hand protection:

Chemically resistant protective gloves. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Neoprene	6 (> 480 minutes)	0,75		EN ISO 374, EN 388
Chemically resistant protective gloves	Polyvinylchloride (PVC)	6 (> 480 minutes)	1,3		EN ISO 374, EN 388

8.2.2.3. Respiratory protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

Respiratory protection			
Device	Filter type	Condition	Standard
Breathing apparatus with filter		Short term exposure	
Self contained breathing apparatus		Long term exposure	

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Slightly yellowish.
Odour	: ammonia.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: 150 °C
Flammability	: Not applicable
Explosive properties	: Product is not explosive. Flammable or explosive vapour/air mixtures may be formed.
Oxidising properties	: Not self-igniting.
Lower explosive limit (LEL)	: 0.6 vol %
Upper explosive limit (UEL)	: 7 vol %
Flash point	: 40 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Water: Not miscible
Partition coefficient n-octanol/water (Log Kow)	: Not available

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

Vapour pressure	: 2.1 hPa (20°C)
Vapour pressure at 50°C	: Not available
Density	: 0.802 g/cm ³ (20°C)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	: 92.8 %
Solvent content	: 14,3 %
Ignition temperature	: 507 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

No data available.

10.3. Possibility of hazardous reactions

alkali metals.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO₂). Phosgene. Hydrogen chloride.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Solvent naphtha (petroleum), light arom. (64742-95-6)

LD50 oral rat	2000 – 5000 mg/kg
---------------	-------------------

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

LD50 oral	5900 mg/kg
LD50 dermal	13000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: May be fatal if swallowed and enters airways.

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

ammonium hydroxide (1336-21-6)

LC50 fish 1	26.8 mg/l
-------------	-----------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Do not flush into surface water or sewer system

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains.
Product/Packaging disposal recommendations	: Must not be disposed together with household garbage. Empty containers should be taken for local recycling, recovery or waste disposal. Packaging that cannot be cleaned should be disposed of like the product.

Switzerland

Waste code (VeVA) : 16 05 08 - [S] Discarded organic chemicals consisting of or containing dangerous substances






Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1993	UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper shipping name				
FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)	Flammable liquid, n.o.s. (Solvent naphtha (petroleum), light arom.)	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)
Transport document description				
UN 1993 FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1993 Flammable liquid, n.o.s. (Solvent naphtha (petroleum), light arom.), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 274, 601
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19
Transport category (ADR) : 3
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E

Transport by sea

Special provisions (IMDG) : 223, 274, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

Packing instructions (IMDG) : LP01, P001
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 274, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 274, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Transport category (RID) : 3
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
28.	Rubisol	Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 92.8 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

Switzerland

- Swiss National Regulations : Article 13 Order on the protection of maternity (RS 822.111.52):
Pregnant women and breastfeeding mothers cannot come into contact with this product (this substance/this preparation) when working except where it has been established, on the basis of a risk analysis performed in accordance with Art. 63 OLT 1 (RS 822.111), that there is no concrete threat to the health of the mother or baby or that said threat can be excluded thanks to the suitable protection measures taken.
- Article 4, subparagraph 4 Order on the protection of young workers (OLT 5, RS 822.115) and Article 1, letter f Order of the DEFR on dangerous works for young workers (822.115.2):
Young workers undergoing initial professional training cannot work with this product (this substance/this preparation) except where envisaged in the order of professional training to achieve the training purposes and if the training plan conditions and applicable age limits are respected. Young workers who do not undergo initial professional training cannot work with this product (this substance/this preparation). Workers of either sex aged under 18 years old are considered as young.
- Water Protection Ordinance (GSchV, SR 814.201) : Class A
- Clean Air Ordinance (LRV, SR 814.318.142.1) : Annex 1, number 7, Class 3
Emission concentration must not exceed the following value: 150 mg/m³
- Accident Ordinance (StFV, SR 814.012) : Annex 1, number 4
Threshold quantity: 20000 kg
- VOC Ordinance (VOCV, SR 814.018) : 92.8 %

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

Abbreviations and acronyms:	
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Rubisol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 12236-0035

Full text of H- and EUH-statements:	
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Expert judgement
Aquatic Chronic 2	H411	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.